



## RACKMOUNT LCD SPECIFICATIONS

<b>Form Factor</b>	1U rack mounting on slide-out rails or 6/7/8/9U
<b>Color</b>	Black
<b>Compatilbity</b>	PCs, SUNs, IBMs, HPs & DELLs
<b>Server-side Interface Monitor</b>	HD15 VGA
<b>Other Options</b>	Touchscreen video input / DC Power
<b>LCDType</b>	Samsung Grade A Industrial TFT LCD Panel
<b>Signal Input</b>	VGA, Analog RGB
<b>Option Video Input</b>	S-Video & Composite Video / DVI-D
<b>LCD MTBF</b>	50,000 hrs
<b>Power</b>	110 or 220 VAC at 50 or 60 Hz via AC adapter (12V, 5A)
<b>Option DC power</b>	12V, 24V or 48V DC input
<b>Temperature</b>	0 to 50 Degree Celsius (Operation) -5 to 65 Degree Celsius (Storage)
<b>Relative Humidity</b>	5~90%, non-condensing
<b>Shock</b>	10G acceleration (11ms duration)
<b>Vibration</b>	5~500Hz 1G RMS random vibration
<b>Agency Approvals</b>	CE, FCC, VCCI, TAA Compliant (**RoHS Compliancy available upon request)
<b>Warranty</b>	2-Year Warranty